

NOTE: CABLE IS CUT TO LENGTH SPECIFIED IN THE PART NUMBER.
LENGTH AFTER ASSEMBLY MAY DIFFER.

REVISIONS

REV	ECR	DESCRIPTION	DRAWN	DATE
1		ENGINEERING RELEASE	M. LARSEN	06/05/2025

CONTACT LTI FOR CUSTOM LENGTH AND TOLERANCE

CABLE LENGTH:
"-X" IN THE ENDING OF THE CABLE PART NUMBER IS
CALLING OUT THE LENGTH THE CABLE IS CUT.
EXAMPLES SHOWN BELOW:

I-PEX MHF 1:
LTI P/N: CB1.13-IPX-SALRMGT-4IN (4 INCHES)
CBG-IPX-SALRMGT-100mm (100 MILLIMETERS)

I-PEX MHF 1 LOCKING:
LTI P/N: CB1.13-IPXLK-SALRMGT-4IN (4 INCHES)
CBG-IPXLK-SALRMGT-100mm (100 MILLIMETERS)





- NOTES:
- 1. OPERATING FREQUENCY: DC - 6GHz
 - 2. IMPEDANCE: 50Ω
 - 3. TEMPERATURE RANGE: -40 °C ~ +90 °C
 - 4. MAX HEIGHT: 2.5mm (MHF 1), 2.9mm (MHF 1 LK)
 - 5. I-PEX CABLE CRIMP STRENGTH: 15N MIN
 - 6. I-PEX DURABILITY: 30 CYCLES
 - 7. CONNECTOR ORIENTATION 0° ± 45°

CABLE PART NUMBERING (MHF 1):
CBX-IPX-SALRMGT-X

CABLE PART NUMBERING (MHF 1 LOCKING):
CBX-IPXLK-SALRMGT-X

IPX® AND MHF® ARE REGISTERED TRADEMARKS OF I-PEX CO., LTD. CORPORATION

(1): CABLE TYPE		(2): IPX (I-PEX MHF 1)	(3): IPXLK (I-PEX MHF 1 LOCKING HARNESS)	(4): RP-SMA PLUG	(5): HEAT SHRINK TUBE	CBL ASSY LENGTH
"1.13"	Ø 1.13mm, CABLE, BLACK	IPXLF11GPB-113 (20278-112R-13)	"1.13" Ø 1.13mm, CABLE, CB1.13-2IPXLK-500MM, BLACK	LTI P/N: SALRM11GT-316 (RP-SMA, PLUG, RIGHT ANGLE, CABLE CRIMP)	Ø 3/32, .5" LENGTH, GREEN	TOLERANCE: 1-36IN ± 0.5 25-915mm ± 13
"1.17LL"	Ø 1.17mm, LOW-LOSS CABLE, GRAY	IPXLF11GPB-113 (20278-112R-13)			Ø 3/32, .5" LENGTH, GREEN	
"1.32D"	Ø 1.32mm, DOUBLE-SHIELD CABLE, GREEN	IPXLF11GPB-132 (20278-112R-32)			Ø 3/32, .5" LENGTH, GREEN	
"1.37"	Ø 1.37mm, CABLE, BLUE	IPXLF11GPB-137 (20351-112R-37)	"1.37" Ø 1.37mm, CABLE, CB1.37-2IPXLK-500MM, BLACK		Ø 3/32, .5" LENGTH, GREEN	
"G"	RG-178, CABLE, COPPER	IPXLF11GPB-178 (20278-112R-18)	"G" RG-178, CABLE, CBG-2IPXLK-500MM, BROWN		Ø 1/8, .75" LENGTH, GREEN	



DO NOT SCALE DRAWING
TOLERANCES UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN MILLIMETERS
X = ±0.5
X.X = ±0.25
X.XX = ±0.13
ANGLE = ±30°
THIRD ANGLE PROJECTION



Lighthouse Technologies

San Diego, CA
WWW.RFCONNECTOR.COM

TITLE:
CABLE ASSEMBLY,
IPX (MHF 1), TO R/A RP-SMA PLUG,
CABLE CRIMP

PROPRIETARY AND CONFIDENTIAL
UNLESS OTHERWISE SPECIFIED: THIS DOCUMENT CONTAINS LIGHTHORSE TECHNOLOGIES INFORMATION.
REPRODUCTION, USE, DISCLOSURE OR TRANSMITTAL OF ALL OR ANY PART OF THIS DOCUMENT IS PROHIBITED
EXCEPT TO THE EXTENT APPROVED IN WRITING BY AN AUTHORIZED REPRESENTATIVE OF LIGHTHORSE
TECHNOLOGIES. LIGHTHORSE TECHNOLOGIES RESERVES ALL RIGHTS UNDER PATENTS, TRADEMARKS,
COPY RIGHTS AND TRADE SECRETS. COPY RIGHTS OF LIGHTHORSE TECHNOLOGIES 2011, ALL RIGHTS RESERVED.



CUSTOMER APPROVAL		
SIGN / DATE:		
ENG APPR.		
CHECKED		
DRAWN	M. LARSEN	06/05/2025
	NAME	DATE

SIZE	PART/DWG. NO:	REV
B	CBX-IPX-SALRMGT-X	1
SCALE: 2:1	FILE NAME	SHEET 1 OF 1