


	Tolerances 1-20=+/-0.2 20-30=+/-0.3 30-40=+/-0.4 40-50=+/-0.5 50-100=+/-0.75 100-300=+/-1.5 Angles=+/-1 Dimensions are in Millimeters	Revisions Description/Approved/Date	Approved M.H.	Date 04/25/02
			Checked M.H.	Date 04/25/02
			Drawn K.R.E.	Date 04/23/02
		NOTES (plating thickness in micro-inches):	5. Per MIL-P-19468 6. Per ZZ-R-765 7. Per WW-T-799 8. Gold pl. 5 min. over nickel pl. 50 min. over copper strike 9. Nickel pl. 100 min. over copper strike 10. Per QQ-P-35 11. Gold pl. 30 min. over nickel pl. 50 min. over copper strike	



ITEM	MATERIAL	FINISH
Connector Body	Brass, Note 1	Gold, Note 8
Center Contact: Female	Phosphor Bronze	Gold, Note 11
Insulation	Teflon, Note 5	None
Ferrule	Annealed Copper, Note 7	Same as body
Gasket	--	--
Hex Nut	--	--
Lock Washer	--	--

 Lighthouse Technologies, Inc. 4907 Morena Boulevard, #1411 San Diego, California 92117		
Part Number: LTI-SCSM11GT-58		
Description SMC crimp type plug receptacle for RG-58 cable.		
Gold plated brass body, teflon dielectric.		
Scale 3:1	Drawing No. SMC/SCSM11-58	File Name SCSM11-58